OTP Οριζόντιο Καλούπι Υψηλής Ακριβειας για Πτύχωση Ακροδεκτών

Model No. JW-AP14



SPECIFICATIONS

Τυπος	Οριζόντιο Καλούπι
Μαρκα	OTP
Εφαρμογή	Πτύχωση Ακροδεκτών Καλωδιών
Σχημα	U
Χρήση	Τερματικες Μηχανες, Πρεσες Ακροδεκτών

Οριζόντιο καλούπι υψηλής ακριβειας OTP, Εφαρμογη πτύχωσης ακροδεκτών καλωδιών, Εργαλειό πρεσας ακροδεκτών, Εφαρμογη πτύχωσης ακροδεκτών, Καλούπι σχηματος U OTP, Εφαρμογη τερματικής μηχανής, Καλούπι Otp, Καλούπι τερματικου Otp, μητρα τερματικου εφαρμοστη Καλούπι OTP Καλούπια οριζόντιας και καθετης πτύχωσης, τερματική εφαρμογή, μητρα, καλούπι OTP, Οριζόντια και καθετα καλούπια πτύχωσης

OTP high precision horizontal mold



Feeding method: horizontal feed
Feeding stroke: 30mm
Slider stroke: 30mm
Scope of application:
It is suitable for high-precision terminal and connection wire manufacturers with very high requirements for crimping. The ingredients are QPQ and heat-treated fine embroidery technology, which can make the product size more accurate, and it is common with JAM, Xinming and terminal machines.



4S-40 pneumatic horizontal die

Feeding stroke: 40mm
Slider stroke: 40mm
Scope of application: suitable for European and American series automatic and semi-automatic crimping equipment, C.H/I.H adjustment accuracy is 0.02mm, suitable for various horizontal terminals

4E-40 pneumatic straight mold



Feeding stroke: 40mm
Slider stroke: 40mm
Scope of application: suitable for European and American series automatic and semi-automatic crimping equipment, C.H/I.H adjustment accuracy is 0.02mm, suitable for various straight terminals